



Stempelfedern

HENNLICH GmbH & Co KG

Baugrößen			Leichte Belastung; Federwege und -kräfte								Bestell- daten
D _h mm	D _d mm	L ₀ mm	R N/mm	s ₁ mm	F ₁ N	s ₂ mm	F ₂ N	s _{max} mm	F _{max} N	Farbe	Artikel Nr.
10,00	5,00	25,0	10,0	6,5	65,0	7,7	77,0	10,3	103,0	grün	SL10x25
		32,0	8,5	8,3	70,5	9,9	84,1	13,1	111,3		SL10x32
		38,0	6,8	9,9	67,3	11,7	79,6	15,6	106,1		SL10x38
		44,0	6,0	11,4	69,0	13,6	81,6	18,0	108,0		SL10x44
		51,0	5,0	13,3	66,5	15,8	79,0	20,9	104,5		SL10x51
		64,0	4,3	16,6	71,4	19,8	85,1	26,0	111,8		SL10x64
		76,0	3,2	19,8	63,4	23,5	75,2	31,2	99,8		SL10x76
		305,0	1,1	79,3	87,2	94,5	103,9	125,0	137,5		SL10x305
12,50	6,30	25,0	17,9	6,5	116,3	7,7	137,8	10,3	184,4	grün	SL13x25
		32,0	16,4	8,3	136,1	9,9	162,4	13,1	214,8		SL13x32
		38,0	13,6	9,9	134,6	11,7	159,1	15,6	212,2		SL13x38
		44,0	12,1	11,5	139,1	13,6	164,6	18,0	217,8		SL13x44
		51,0	11,4	13,3	151,6	15,8	180,1	20,9	238,3		SL13x51
		64,0	9,3	16,6	154,4	19,8	184,1	26,3	244,6		SL13x64
		76,0	7,1	19,8	140,6	23,5	166,8	31,2	221,5		SL13x76
		89,0	5,4	23,1	124,7	27,6	149,0	36,5	197,1		SL13x89
305,0	1,4	79,3	111,0	94,5	132,3	125,0	175,0	SL13x305			
16,00	8,00	25,0	23,4	6,5	152,1	7,7	180,2	10,3	241,0	grün	SL16x25
		32,0	22,9	8,3	190,1	9,9	226,7	13,1	300,0		SL16x32
		38,0	19,3	9,9	191,1	11,7	225,8	15,6	301,1		SL16x38
		44,0	17,1	11,5	196,6	13,6	232,6	18,0	307,8		SL16x44
		51,0	15,7	13,3	208,8	15,8	248,1	20,9	328,1		SL16x51
		64,0	10,7	16,6	177,6	19,8	211,9	26,3	281,4		SL16x64
		76,0	10,0	19,8	198,0	23,5	235,0	31,2	312,0		SL16x76
		89,0	8,6	23,1	198,7	27,6	237,4	36,5	313,9		SL16x89
102,0	7,8	26,5	206,7	31,6	246,5	41,8	326,0	SL16x102			
305,0	2,5	79,3	198,2	94,5	236,2	125,0	312,5	SL16x305			
20,00	10,00	25,0	55,8	6,5	362,7	7,7	429,7	10,2	569,2	grün	SL20x25
		32,0	45,0	8,3	373,5	9,9	445,5	12,5	562,5		SL20x32
		38,0	33,3	9,9	329,7	11,7	389,6	15,0	499,5		SL20x38
		44,0	30,0	11,5	345,0	13,6	408,0	18,0	540,0		SL20x44
		51,0	24,5	13,3	325,8	15,8	387,1	20,0	490,0		SL20x51
		64,0	20,0	16,6	332,0	19,8	396,0	25,0	500,0		SL20x64
		76,0	16,0	19,8	316,8	23,5	376,0	30,0	480,0		SL20x76
		89,0	14,0	23,1	323,4	27,6	386,4	35,0	490,0		SL20x89
		102,0	12,0	26,5	318,0	31,6	379,2	41,0	492,0		SL20x102
		115,0	10,9	30,0	327,0	35,6	388,0	46,0	501,4		SL20x115
		127,0	9,5	33,0	313,5	39,4	374,3	51,0	484,5		SL20x127
		139,0	8,4	36,1	303,2	43,1	362,0	56,0	470,4		SL20x139
		152,0	7,5	39,5	296,2	47,1	353,3	61,0	457,5		SL20x152
305,0	4,0	79,3	317,2	94,5	378,0	122,0	488,0	SL20x305			
25,00	12,50	25,0	100,0	6,5	650,0	7,7	770,0	10,2	1020,0	grün	SL26x25
		32,0	80,3	8,3	666,5	9,9	795,0	12,5	1003,8		SL26x32
		38,0	62,0	9,9	613,8	11,7	725,4	15,0	930,0		SL26x38
		44,0	52,9	11,5	608,3	13,6	719,4	18,0	952,2		SL26x44
		51,0	44,0	13,3	585,2	15,8	695,2	20,0	880,0		SL26x51
		64,0	35,2	16,6	584,3	19,8	697,0	25,0	880,0		SL26x64
		76,0	28,0	19,8	554,4	23,5	658,0	30,0	840,0		SL26x76
		89,0	24,0	23,1	554,4	27,6	662,4	35,0	840,0		SL26x89
		102,0	21,1	26,5	559,1	31,6	666,8	41,0	865,1		SL26x102
		115,0	18,7	30,0	561,0	35,6	665,7	46,0	860,2		SL26x115
		127,0	16,7	33,0	551,1	39,4	658,0	51,0	851,7		SL26x127
		139,0	15,3	36,1	552,3	43,1	659,4	56,0	856,8		SL26x139
		152,0	14,0	39,5	553,0	47,1	659,4	61,0	854,0		SL26x152
		178,0	12,5	46,3	578,7	55,2	690,0	71,0	887,5		SL26x178
		203,0	10,4	52,8	549,1	62,9	654,2	81,0	842,4		SL26x203
305,0	7,0	79,3	551,9	94,5	657,7	122,0	849,1	SL26x305			

Stempelfedern

HENNLICH GmbH & Co KG

Baugrößen			Leichte Belastung; Federwege und -kräfte								Bestell-			
D _h mm	D _d mm	L ₀ mm	R N/mm	s ₁ mm	F ₁ N	s ₂ mm	F ₂ N	s _{max} mm	F _{max} N	Farbe	Artikel Nr.			
32,00	16,00	38,0	94,0	9,9	930,6	11,7	1099,8	15,0	1410,0	grün	SL32x38			
		44,0	79,5	11,5	914,3	13,6	1081,2	18,0	1431,0		SL32x44			
		51,0	67,0	13,3	891,1	15,8	1058,6	20,0	1340,0		SL32x51			
		64,0	53,0	16,6	879,8	19,8	1049,4	25,0	1325,0		SL32x64			
		76,0	44,0	19,8	871,2	23,5	1034,0	30,0	1320,0		SL32x76			
		89,0	37,2	23,1	859,3	27,6	1026,7	35,0	1302,0		SL32x89			
		102,0	32,0	26,5	848,0	31,6	1011,2	41,0	1312,0		SL32x102			
		115,0	29,0	30,0	870,0	35,6	1032,4	46,0	1334,0		SL32x115			
		127,0	25,0	33,0	825,0	39,4	985,0	51,0	1275,0		SL32x127			
		139,0	23,0	36,1	830,3	43,1	991,3	56,0	1288,0		SL32x139			
		152,0	21,5	39,5	849,3	47,1	1012,6	61,0	1311,5		SL32x152			
		178,0	18,2	46,3	842,7	55,2	1004,6	71,0	1292,2		SL32x178			
		203,0	15,8	52,8	834,2	62,9	993,8	81,0	1279,8		SL32x203			
254,0	12,5	66,0	825,0	78,7	983,7	102,0	1275,0	SL32x254						
		305,0	10,3	79,3	816,8	94,5	973,4	122,0	1256,6		SL32x305			
40,00	20,00	51,0	92,0	13,3	1223,6	15,8	1453,6	20,0	1840,0	grün	SL40x51			
		64,0	73,0	16,6	1211,8	19,8	1445,4	25,0	1825,0		SL40x64			
		76,0	63,0	19,8	1247,4	23,5	1480,5	30,0	1890,0		SL40x76			
		89,0	51,0	23,1	1178,1	27,6	1407,6	35,0	1785,0		SL40x89			
		102,0	43,0	26,5	1139,5	31,6	1358,8	41,0	1763,0		SL40x102			
		115,0	39,6	30,0	1188,0	35,6	1409,8	46,0	1821,6		SL40x115			
		127,0	37,0	33,0	1221,0	39,4	1457,8	51,0	1887,0		SL40x127			
		139,0	32,0	36,1	1155,2	43,1	1379,2	56,0	1792,0		SL40x139			
		152,0	28,0	39,5	1106,0	47,1	1318,8	61,0	1708,0		SL40x152			
		178,0	25,2	46,3	1166,8	55,2	1391,0	71,0	1789,2		SL40x178			
		203,0	22,7	52,8	1198,6	62,9	1427,8	81,0	1838,7		SL40x203			
		254,0	17,0	66,0	1122,0	78,7	1337,9	102,0	1734,0		SL40x254			
				305,0	14,8	79,3	1173,6	94,5	1398,6		122,0	1805,6		SL40x305
50,00	25,00	64,0	156,0	16,6	2589,6	19,8	3088,8	25,0	3900,0	grün	SL51x64			
		76,0	125,0	19,8	2475,0	23,5	2937,5	30,0	3750,0		SL51x76			
		89,0	109,0	23,1	2517,9	27,6	3008,4	35,0	3815,0		SL51x89			
		102,0	94,0	26,5	2491,0	31,6	2970,4	41,0	3854,0		SL51x102			
		115,0	81,0	30,0	2430,0	35,6	2883,6	46,0	3726,0		SL51x115			
		127,0	71,0	33,0	2343,0	39,4	2797,4	51,0	3621,0		SL51x127			
		139,0	66,5	36,1	2400,7	43,1	2866,2	56,0	3724,0		SL51x139			
		152,0	60,0	39,5	2370,0	47,1	2826,0	61,0	3660,0		SL51x152			
		178,0	52,0	46,3	2407,6	55,2	2870,4	71,0	3692,0		SL51x178			
		203,0	44,0	52,8	2323,2	62,9	2767,6	81,0	3564,0		SL51x203			
		254,0	35,0	66,0	2310,0	78,7	2554,5	102,0	3570,0		SL51x254			
				305,0	28,5	79,3	2260,1	94,5	2693,3		122,0	3477,0		SL51x305
		63,00	38,00	76,0	189,0	19,8	3742,2	23,5	4441,5		30,0	5670,0	grün	SL63x76
89,0	158,0			23,1	3649,8	27,6	4360,8	35,0	5530,0	SL63x89				
102,0	131,0			26,5	3471,5	31,6	4139,6	41,0	5371,0	SL63x102				
115,0	116,0			30,0	3480,0	35,6	4129,6	46,0	5336,0	SL63x115				
127,0	103,0			33,0	3399,0	39,4	4058,2	51,0	5253,0	SL63x127				
152,0	84,3			39,5	3329,9	47,1	3970,5	61,0	5142,3	SL63x152				
178,0	71,5			46,3	3310,5	55,2	3946,8	71,0	5076,5	SL63x178				
203,0	61,7			52,8	3257,8	62,9	3880,9	81,0	4997,7	SL63x203				
254,0	47,0			66,0	3102,0	78,7	3698,9	102,0	4794,0	SL63x254				
		305,0	38,2	79,3	3029,3	94,5	3609,9	122,0	4660,4		SL63x305			